

# Burbuja

**R10 RTK GPS**

### Características principales:

Horizontal

vertical

11

## Bluetooth

(Bluetooth®) 10

Transmisión de potencia: 2W

15 mm de 0.5ppm rms

## Encuesta estática GNSS

□□□□□□□□□□

### Tiempo de inicio de RTK especificado

**vertical**

## Almacenamiento de datos

## Horizontal

Compass: B1, B2, B3

□□□□□

## Antena GNSS intelligente

□ □ □ □ □ □ □ □ □

## Horizontal

## Medidas rápidas y precisas

Rango de 410 MHz a 470 MHz:

vertical

RTK610 mm/min rms

Estática y rápida estática

vertical

especificación

Un nuevo nivel de productividad

Colocación

Banda ancha de 450MHz cerrada

GNSS

Trimble R10 RTK GPS

Seguimiento de señales satelitales

3.5 mm 0.4ppm rms

Soporte L5)

Normal <5 m 3drms

3 mm de 0.1ppm rms

vertical

Precisión 4

Horizontal

L5

3 mm de 0.5ppm rms

B1 B2 B3

Precisión 2

2-8 segundos

14 satélites

0.25m 1ppm rms

Horizontal

0.50m 1ppm rms

SBA

<5 m 3drms

2

## GNSS

3 mm de 0.1ppm rms	
3.5 mm 0.4ppm rms	
3 mm de 0.5ppm rms	
5 mm de 0.5ppm rms	

## Horizontal

8 mm 1 ppm rms	
15 mm 1ppm rms	
8 mm de 0.5ppm rms	
15 mm de 0.5ppm rms	
2 8	
Rtk610 mm/ rms	
RTK620 mm/ rms	

## Especificaciones de rendimiento

8 mm 1 ppm RMS

15 mm 1ppm rms

450MHz

Webui

410 MHz 470 MHz

RTK620 mm/min rms

Trimble xfill5

Posicionamiento diferencial SBAS

tecnología

(Bluetooth®) 10

Red RTK3

5 mm de 0.5ppm rms  
al mismo tiempo

Rendimiento de posicionamiento

0.25m 1ppm RMS

14

0.50m 1ppm RMS

8 mm de 0.5ppm rms

WebUI

2 W

detección

Estática de alta precisión

medición

Bluetooth

# TRIMBLE R10 GNSS SYSTEM

## KEY FEATURES

Cutting-edge **Trimble HD-GNSS** processing engine

Precise position capture with **Trimble SurePoint** technology

New **Trimble xFill** technology provides RTK coverage during connection outages

Advanced satellite tracking with **Trimble 360** receiver technology

Sleek ergonomic design for easier handling



## A NEW LEVEL OF PRODUCTIVITY

The first of its kind, the new Trimble® R10 System is designed to help surveying professionals work more effectively. With powerful new technologies like Trimble HD-GNSS, Trimble SurePoint™, and Trimble xFill™ integrated into a new sleek design, this powerful system goes beyond comprehensive GNSS support to ensure surveyors have the ability to collect more accurate data faster and easier—no matter what the job or the environment.

## TRIMBLE HD-GNSS PROCESSING ENGINE A new generation of core positioning technology

Integrated into the Trimble R10 is the advanced Trimble HD-GNSS processing engine. This ground-breaking technology transcends traditional fixed/float techniques to provide a more accurate assessment of error estimates than traditional GNSS technology, especially in challenging environments. Markedly reduced convergence times as well as high position and precision reliability enable surveyors to collect measurements with confidence while reducing their occupation time.

## TRIMBLE SUREPOINT TECHNOLOGY Simplifying the survey workflow

Trimble SurePoint technology incorporated into the Trimble R10 system provides users with faster measurements, increased accuracy, and greater quality control.

## An Electronic Bubble

The Trimble R10 system employs an electronic bubble that appears on the Trimble controller display. With this new eBubble, all measurement information is displayed in one place and users don't have to switch focus from the controller screen to the pole bubble to check that the pole is plumb.

## Rapid, Accurate Measurement

Trimble SurePoint technology displays the eBubble in green when the pole is plumb, clearly indicating that an accurate measurement is possible. The system constantly monitors pole tilt for the user. If a point is measured with pole tilt beyond a user-defined setting, Trimble Access™ software will alert the user and prompt them to accept or discard the point. SurePoint even uses the pole tilt as a controlling input. After a point is measured, tilting the pole causes the system to automatically prepare to measure the next point.

## Data Traceability

As insurance that all of your data is traceable, the Trimble R10 can record the pole tilt information for measured points. These records include the pole tilt angle and the distance on the ground represented by that pole tilt angle.

## TRIMBLE 360 RECEIVER TECHNOLOGY Future Proof Your Investment

Powerful Trimble 360 receiver technology in the Trimble R10 supports signals from all existing and planned GNSS constellations and augmentation systems. With two integrated Trimble Maxwell™ 6 chips the Trimble R10 offers an unparalleled 440 GNSS channels. Trimble delivers business confidence with a sound GNSS investment for today and long into the future.

## TRIMBLE xFILL TECHNOLOGY

### More continuous surveying, less downtime

Continue surveying without interruption when you temporarily lose connection to your base station or Trimble VRS™ network. Leveraging a worldwide network of Trimble GNSS reference stations and satellite datalinks, Trimble xFill works to seamlessly 'fill in' for gaps in your RTK or VRS correction stream.

## ERGONOMICALLY DESIGNED Easier Handling and Operation

As the smallest and lightest integrated receiver in its class, the Trimble R10 system is ergonomically designed to provide the surveyor with effortless handling and operation. Designed for ease of use, the progressive design incorporates a more stable center of mass at the top of the range pole, while its sleeker, taller profile provides the durability and reliability for which Trimble is known.

The Trimble R10 receiver incorporates a quick release adaptor for simple and safe removal of the receiver from the range pole. Additionally, the quick release adaptor ensures a solid, stable connection between the range pole and receiver.

## AN INTELLIGENT SOLUTION

Advanced features combined with the powerful technology in the Trimble R10 make this the most intelligent GNSS system on the market today.

## Smart GNSS Antenna

Survey with confidence—the Trimble R10 system's GNSS antenna tracks GNSS and SBAS signal bands. Its Trimble Stealth™ Ground Plane mitigates multipath signals by using electrical resistance to keep unwanted signals from reaching the antenna element.

## Smart Battery

A smart lithium-ion battery inside the Trimble R10 system delivers extended battery life and more reliable power. A built-in LED display allows the user to quickly check remaining battery life.

## Advanced Communication Capabilities

The Trimble R10 system uses the latest mobile phone technology to receive VRS corrections and connect to the Internet from the field. Then, access Trimble Connected Community to send or receive documents while away from the office. Using WiFi, easily connect to the Trimble R10 system using a laptop or smartphone to configure the receiver without a Trimble controller.

## The Trimble system of hardware and software that's known and trusted

Bring the power and speed of the Trimble R10 system together with trusted Trimble software solutions, including Trimble Access and Trimble Business Center, to get the most complete, intelligent solution. Trimble Access field software provides specialized and customized workflows to make surveying tasks quicker and easier while enabling teams to communicate vital information between field and office in real-time. Back in the office, users can seamlessly process data with Trimble Business Center office software.

The Trimble R10 GNSS system, a new era of surveying productivity beyond GNSS for professional surveyors.





# TRIMBLE R10 GNSS SYSTEM

## DATASHEET

### PERFORMANCE SPECIFICATIONS

#### Measurements

- Measuring points sooner, faster and in harsh environments with Trimble HD-GNSS technology
- Increased measurement traceability with Trimble SurePoint electronic plumb detection
- Reduced downtime due to loss of radio signal with xFill technology
- Advanced Trimble Maxwell 6 Custom Survey GNSS chips with 440 channels
- Future-proof your investment with Trimble 360 GNSS tracking
- Satellite signals tracked simultaneously:
  - GPS: L1C/A, L1C, L2C, L2E, L5
  - GLONASS: L1C/A, L1P, L2C/A, L2P, L3
  - SBAS: L1C/A, L5 (For SBAS satellites that support L5)
  - Galileo: GIOVE-A and GIOVE-B, E1, E5a, E5B
  - COMPASS: B1, B2, B3
- OmniSTAR HP, XP, G2, VBS positioning
- QZSS, WAAS, MSAS, EGNOS, GAGAN
- Positioning Rates: 1 Hz, 2 Hz, 5 Hz, 10 Hz, and 20 Hz

### POSITIONING PERFORMANCE<sup>1</sup>

#### Code differential GNSS positioning

Horizontal	0.25 m + 1 ppm RMS
Vertical	0.50 m + 1 ppm RMS
SBAS differential positioning accuracy <sup>2</sup>	typically <5 m 3DRMS

#### Static GNSS surveying

##### High-Precision Static

Horizontal	3 mm + 0.1 ppm RMS
Vertical	3.5 mm + 0.4 ppm RMS

#### Static and Fast Static

Horizontal	3 mm + 0.5 ppm RMS
Vertical	5 mm + 0.5 ppm RMS

#### Real Time Kinematic surveying

##### Single Baseline <30 km

Horizontal	8 mm + 1 ppm RMS
Vertical	15 mm + 1 ppm RMS

#### Network RTK<sup>3</sup>

Horizontal	8 mm + 0.5 ppm RMS
Vertical	15 mm + 0.5 ppm RMS
RTK start-up time for specified precisions <sup>4</sup>	2 to 8 seconds

#### Trimble xFill<sup>5</sup>

Horizontal	.RTK <sup>6</sup> + 10 mm/minute RMS
Vertical	.RTK <sup>6</sup> + 20 mm/minute RMS

1 Precision and reliability may be subject to anomalies due to multipath, obstructions, satellite geometry, and atmospheric conditions. The specifications stated recommend the use of stable mounts in an open sky view, EMi and multipath clean environment, optimal GNSS constellation configurations, along with the use of survey practices that are generally accepted for performing the highest-order surveys for the applicable application including occupation times appropriate for baseline length. Baselines longer than 30 km require precise ephemeris and occupations up to 24 hours may be required to achieve the high precision static specification.

2 Depends on WAAS/EGNOS system performance.

3 Network RTK PPM values are referenced to the closest physical base station.

4 May be affected by atmospheric conditions, signal multipath, obstructions and satellite geometry. Initialization reliability is continuously monitored to ensure highest quality.

5 Precisions are dependent on GNSS satellite availability. xFill positioning ends after 5 minutes of radio downtime. When using a single base station, xFill requires the location of the base antenna to be within 1 m of the base coordinate in a known global reference frame such as WGS-84. When establishing a single base station using the "Here" key in Trimble Access software, the required accuracy is usually only achieved when the position is augmented with WAAS or EGNOS. VRS subscribers should check with their network administrator that the network is setup in a known coordinate system.

6 RTK refers to the last reported precision before the correction source was lost and xFill started.

7 Receiver will operate normally to -40 °C, internal batteries are rated to -20 °C.

8 Varies with temperature and wireless data rate. When using a receiver and internal radio in the transmit mode, it is recommended that an external 6 Ah or higher battery is used.

9 Varies with terrain and operating conditions.

10 Bluetooth type approvals are country specific.

### HARDWARE

#### Physical

Dimensions (W×H)	11.9 cm x 13.6 cm (4.6 in x 5.4 in)
Weight	1.12 kg (2.49 lb) with internal battery, internal radio with UHF antenna, 3.57 kg (7.86 lb) items above plus range pole, controller & bracket
Temperature <sup>7</sup>	
Operating	-40 °C to +65 °C (-40 °F to +149 °F)
Storage	-40 °C to +75 °C (-40 °F to +167 °F)
Humidity	100%, condensing
Ingress Protection	IP67 dustproof, protected from temporary immersion to depth of 1 m (3.28 ft)
Shock and vibration	Tested and meets the following environmental standards:
Shock	Non-operating: Designed to survive a 2 m (6.6 ft) pole drop onto concrete. Operating: to 40 G, 10 msec, sawtooth
Vibration	MIL-STD-810F, FIG.514.5C-1

#### Electrical

- Power 11 to 24 V DC external power input with over-voltage protection on Port 1 and Port 2 (7-pin Lemo)
- Rechargeable, removable 7.4 V, 3.7 Ah Lithium-ion smart battery with LED status indicators.
- Power consumption is 5.1 W in RTK rover mode with internal radio.
- Operating times on internal battery<sup>8</sup>:
  - 450 MHz receive only option: 5.5 hours
  - 450 MHz receive/transmit option (0.5 W): 4.5 hours
  - 450 MHz receive/transmit option (2.0 W): 3.7 hours
  - Cellular receive option: 5.0 hours

### COMMUNICATIONS AND DATA STORAGE

- Serial: 3-wire serial (7-pin Lemo)
- USB: supports data download and high speed communications
- Radio Modem: fully integrated, sealed 450 MHz wide band receiver/transmitter with frequency range of 410 MHz to 470 MHz:
  - Transmit power: 2 W
  - Range: 3–5 km typical / 10 km optimal<sup>9</sup>
- Cellular: integrated, 3.5 G modem, HSDPA 7.2 Mbps (download), GPRS multi-slot class 12, EDGE multi-slot class 12, UMTS/HSDPA (WCDMA/FDD) 850/1900/2100MHz, Quad-band GSM 850/900/1800/1900 MHz, GSM CSD, 3GPP LTE
- Bluetooth: fully integrated, fully sealed 2.4 GHz communications port (Bluetooth<sup>®</sup>)<sup>10</sup>
- WiFi: 802.11 b,g, access point and client mode, WEP64/WEP128 encryption
- External communication devices for corrections supported on – Serial, USB, Ethernet, and Bluetooth ports
- Data storage: 4 GB internal memory; over three years of raw observables (approx. 1.4 MB /day), based on recording every 15 seconds from an average of 14 satellites
- CMR+, CMRx, RTCM 2.1, RTCM 2.3, RTCM 3.0, RTCM 3.1 input and output
- 24 NMEA outputs, GSOF, RT17 and RT27 outputs

#### WebUI

- Offers simple configuration, operation, status, and data transfer
- Accessible via WiFi, Serial, USB, and Bluetooth

### CERTIFICATIONS

FCC Part 15 (Class B device), 22, 24; R&TTE CE Mark; C-Tick, A-Tick; PTCRB; WFA

Contact your local Trimble Authorized Distribution Partner for more information.

Specifications subject to change without notice.



© 2012, Trimble Navigation Limited. All rights reserved. Trimble and the Globe & Triangle logo are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. Access, Maxwell, Stealth, SurePoint, VRS, and xFill are trademarks of Trimble Navigation Limited. All other trademarks are the property of their respective owners. PN 022543-544A (10/12)

TRIMBLE AUTHORIZED DISTRIBUTION PARTNER

### NORTH AMERICA

Trimble Navigation Limited  
10355 Westmoor Dr  
Westminster CO 80021  
USA

### EUROPE

Trimble Germany GmbH  
Am Prime Parc 11  
65479 Raunheim  
GERMANY

### ASIA-PACIFIC

Trimble Navigation  
Singapore Pty Limited  
80 Marine Parade Road  
#22-06, Parkway Parade  
Singapore 449269  
SINGAPORE

