

GO120-D



GO120-D is a portable, self-contained, and easy-to-use system for the detection and identification of leaks in industrial systems. It is designed for use in a wide range of applications, from small-scale leaks to large-scale leaks in complex systems. The system is composed of several key components, including a main unit, a control panel, and a gas detector. The main unit is a large, cylindrical tank that houses the detection and identification system. The control panel is a small, portable unit that allows the operator to monitor and control the system. The gas detector is a small, portable unit that detects the presence of leaks in the system.

GO120-D

GO120-D



GO120-D is a portable, self-contained, and easy-to-use system for the detection and identification of leaks in industrial systems. It is designed for use in a wide range of applications, from small-scale leaks to large-scale leaks in complex systems. The system is composed of several key components, including a main unit, a control panel, and a gas detector. The main unit is a large, cylindrical tank that houses the detection and identification system. The control panel is a small, portable unit that allows the operator to monitor and control the system. The gas detector is a small, portable unit that detects the presence of leaks in the system.

GO120-D is a portable, self-contained, and easy-to-use system for the detection and identification of leaks in industrial systems. It is designed for use in a wide range of applications, from small-scale leaks to large-scale leaks in complex systems. The system is composed of several key components, including a main unit, a control panel, and a gas detector. The main unit is a large, cylindrical tank that houses the detection and identification system. The control panel is a small, portable unit that allows the operator to monitor and control the system. The gas detector is a small, portable unit that detects the presence of leaks in the system.



1. The system is designed for use in a wide range of applications, from small-scale leaks to large-scale leaks in complex systems.
2. The system is composed of several key components, including a main unit, a control panel, and a gas detector.
3. The system is designed for use in a wide range of applications, from small-scale leaks to large-scale leaks in complex systems.

4. 5.5 OLED



- 1. UV
- 2. 80 1
- 3.
- 4. 1mm
- 5. AC220V 3KW 5KW
- 6. 3

	CA1	Ca2	Ca3
mm	200	300	400
mm	300	450	600