

□□□□ -800S GNSS □□□□



▶ ☐ ☐ ☐ ☐ ☐

[illegible]

- [illegible]

[illegible][illegible]

□□□□□□	
□□ □□□MHz□	GPS L1/L2X5 BDS B1B2B3 GRONUS L1L2L3 GAUREO EL/E5A □ E5bE6 □□□□□□□L5 QZSS L1/L2 "L5/L6 IRNSS L5 L□□□
□□□□DB□	5.5
□□□□AR□DB□	<3.0
□□□□□□□	360°
VSWR	<2.0
□□□□□□□□□mm□	±2
□□	□□□□□
□□□□□□□□□□	50Q
□□□□	
LNA□□□□DB□	40±2
□□□□□db□	<2
VSWR	<2.0
□□□□□□□□□□□db□	±2
□□□□□V□	33-12.0
□□□□□MA□	<45
□□□□□□□NS□	<5
r □□□□□	
□□□□□□□□	TNC-K
□□□□□□□□□mm□	^154*64.2
□□□g□	420
□□□□ □ □□□	
□□□□□°C□	-40□85
□□□□□°C□	-55□85

||

|IP67

Shenzhen Ping Kim Technology Co.,Ltd
||
||
||

||
||8615814632339 QQ||2850187683 ||pjk@pjkcn.com
||602||A||Shenzhen