

□□□□□□□□ **FEM-1000V**□□□□

[illegible]

□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □



- FEM-1000V
-
-
-
-
-



- 温度精度 $\pm 1\%$ 分辨率 800mPas 1mPas 精度 1% 量程
- 压力精度 $\pm 0.1\%$ 分辨率 1mPas 精度 0.1% 量程
- 流量精度 $\pm 1\%$ 分辨率 3 位 精度 1% 量程

品名	規格	材質	品番
	仕様		
FEM-1000V-EX品番	FVM80A-PEXG	ExdIICT6	TC18354
	FEM-1000-EXSC	ExdIICT6	TC18851
FEM-1000V-EXMT品番	FVM80A-PEMT	ExdIICT3	TC18356
	FEM-1000-EXSC	ExdIICT6	TC18851

- PLL



-





- [illegible]



□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □



Page 1 of 1

[illegible]

*□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□



電圧		電圧範囲		
電圧		FEM-1000V-ST	FEM-1000V-MT	FEM-1000HV
電圧		電圧		
電圧		電圧/電圧		
電圧	電圧	L電圧	0.50V/1000mPa	-
		M電圧	10.0V/5000mPa	-
		H電圧	500V/20000mPa	-
		HV電圧	-	1.00V/100Pa
	電圧	L電圧	±1%(電圧)	-
		M電圧	±1%(電圧)	-
		H電圧	±1%(電圧)	-
		HV電圧	-	±1V F.S.
	電圧	L電圧	±1%(電圧)	-
		M電圧	±1%(電圧)	-
		H電圧	±1%(電圧)	-
		HV電圧	-	±1V F.S.
電圧		0V/70°C	0V/150°C	0V/150°C
電圧		0V/100°C	0V/180°C	0V/180°C
電圧		電圧 (JIS Z8809-2011)		
電圧		電圧4V/20mA (電圧16bit) RS232C		
電圧		10V/40°C/20V/80%RH (電圧)		
電圧		AC100V/240V 50V/60Hz		
電圧	電圧	FVM80A-PST	FVM80A-PMT	FEM-1000-PMT
	電圧	FEM-1000V-STC		
	電圧	電圧←電圧 L=5m 電圧←電圧 L=2.5m		
電圧		-		

□□□	□□□□□□□□□□		
□□□□	FEM-1000V-EX	FEM-1000V-EXMT	FEM-1000HV-EX

項目		項目	Exd II CT6	Exd II CT3	Exd II BT3
		測定/測定範囲	Exd II BT6		
圧	測定	L値	0.50[1000mPa]s		-
		M値	10.0[5000mPa]s		-
		H値	500[20000mPa]s		-
		HV値	-		1.00[100Pa]s
	精度	L値	±1%(測定値)		-
		M値	±1%(測定値)		-
		H値	±1%(測定値)		-
		HV値	-		±1[F.S.]
	精度	L値	±1%(測定値)		-
		M値	±1%(測定値)		-
		H値	±1%(測定値)		-
		HV値	-		±1[F.S.]
測定範囲		0[70℃	0[150℃	0[150℃	
		0[100℃	0[180℃	0[150℃	
測定範囲		測定範囲(測定範囲) (JIS Z8809-2011)			
測定範囲		測定範囲4[20mA測定範囲] (測定範囲16bit)測定範囲RS232C測定範囲測定範囲			
測定範囲		10[40℃[20[80%RH(測定範囲)			
測定範囲		DC24V			
測定範囲	測定範囲	FVM80A-PEXG	FVM80A-PEMT	FEM-1000-PEMT	
	測定範囲	FEM-1000-EXSC測定範囲測定範囲/SMC-1000V測定範囲測定範囲			
	測定範囲	測定範囲測定範囲 L = 5m 測定範囲3[3]			
測定範囲		-			