

## Inspect pipes faster to complete more surveys each day

- The intuitive interface is quick to set up and simple to operate.
- Dedicated function keys make it easy to use.
- Built-in rechargeable batteries lasting all day.

## Stay connected

Reports are ready to share as soon as your survey is complete.

- WiFi connection for sending reports via DropBox or email.
- Advanced connectivity with USB, HDMI and ethernet, making it easy to view and export your data.
- Video streaming to nearby devices.

## A suite of reporting formats

Expand your client base by offering a variety of tailored surveys through

- MSCC3, 4 & 5 compliant reports.
- WinCan compatible files.
- Basic reports

## Customised solutions

- Modular by design, the flexitrax P550c system can be paired with a range of products and accessories.
- Our solution gives you flexibility when you need it, enabling you to survey pipes from 1¼" / 32mm to 60" / 1500mm.



## flexitrap P550c controller



## Drums



## Easier. Faster. Simpler.

The flexitrap P550c is designed around simplicity of operation. Ready to use in 30 seconds from powering on, it requires minimal training to operate, letting you concentrate on pipe inspection.

A large 12.1" / 307mm HD, daylight visible screen combined with full-size keyboard and dedicated function keys guide you through the survey process, making the system faster and easier to use.

Built in is a high capacity internal lithium-ion battery, providing power for up to a full day's typical usage, and 128Gb of solid state memory, sufficient for over 90 hours of video recording.

### **Tailored solutions**

This portable and modular crawler system enables operators to customise the flexitrap P550c solution for the inspection of a vast range of pipes, in all locations.

The flexitrap P550c can be readily transported and easily wheeled onto site through our rugged, ergonomic design, allowing you to reach access points beyond the range of your vehicle.

### **Survey an extensive range of pipes**

Survey pipes as small as 1 1/4" / 32mm or as large as 60" / 1500mm.